


BLM Sleeve Applicators

Features

Standard

- Mild Steel – Epoxy Paint
- Certified Electrical Enclosures
- Up to 50 cpm*
- > D: 1 pint to 2.5 gallons (300ml. to 10 liters)
- > Dy >: 1.25 gallons to 7.5 gallons (5 to 30 liters)
- 480 VAC 3 ph. 60Hz - 5 KW
- 5 bars – 70 PSI
- Allen Bradley PLC, HMI, Servos



Measurements are in meters – 1 meter = 3.28ft

Features including optionals

Sturdy Mechanical Design
Epoxy Painted Frame
(Stainless Steel Optional)
Full Enclosure
Single Unwind Reel

Dual Speed Control
Safety Interlocks
Keyed Run/Jog Switch
Electrical Lock Out/Tag Out
PLC Control
Remote Jog
Status Indicator Light Bank

Upstream Photo Eyes
Downstream Photo Eyes
Low Material Sensor
Film Application Jam Sensor
Material Out Sensor

Direct Mandrel Application
Compact Design
Fits Most Existing Lines
Single Head In-Line Operation
Made in France using
Off-the-Shelf Components
Complete Documentation

System parameters for speed and size range are designed to best suit the initial project requirements.

Running outside these parameters may require parts or machine modifications

** Speeds depending on specific model and needs to be confirmed upon testing*

o š Z ~ < v •

1486, rue JB Michaud
Drummondville, J2C 7V3, Qc
Phone 514-941-8266
Email: info@celtheq.com
www.celtheq.com